

<b>THOMSON</b> <b>DELPHION</b>		<b>RESEARCH</b>	<b>PRODUCTS</b>	<b>INSIDE DELPHION</b>
<a href="#">My Account</a>   <a href="#">Products</a>	Search: <a href="#">QuickNumber</a> <a href="#">Boolean</a> <a href="#">Advanced</a>			

## The Delphion Integrated View

Get Now: <input checked="" type="checkbox"/> PDF   <a href="#">More choices...</a>	Tools: Add to Work File: <a href="#">Create new Wo</a>
View: <a href="#">INPADOC</a>   Jump to: <a href="#">Top</a>	Go to: <a href="#">Derwent...</a>

🔍 Title: **JP2002216733A2: SEPARATOR FOR SEALED LEAD-ACID BATTER MANUFACTURING METHOD FOR IT**

🔍 Country: JP Japan  
 🔍 Kind: A2 Document Laid open to Public inspection I

🔍 Inventor: **ENDO HIDEO;  
 MATSUNAMI TAKAAKI;  
 SHIMIZU MAKOTO;**

🔍 Assignee: **NIPPON MUKI CO LTD**  
[News, Profiles, Stocks and More about this company](#)

🔍 Published / Filed: **2002-08-02 / 2001-01-17**

🔍 Application Number: **JP2001000008851**

🔍 IPC Code: **H01M 2/16; H01M 10/12;**

🔍 Priority Number: **2001-01-17 JP2001000008851**

🔍 Abstract:

**PROBLEM TO BE SOLVED:** To increase the quantity of inorganic powder and hold down the quantity of inorganic powder passing through into water in a separator which is wet mixed with mainly using fine glass fiber and inorganic material containing inorganic powder.

**SOLUTION:** This separator for a sealed lead-acid battery is made by wet mixing mainly the fine glass fiber and inorganic material containing inorganic powder. The inorganic materials are connected to each other by an inorganic coagulant.

**COPYRIGHT:** (C)2002,JPO

🔍 Family: None

🔍 Other Abstract Info: **CHEMABS 137(08)111745P DERABS C2003-106141**



[Nominate](#)

[this for the Gallery...](#)